# **™** K©A Couplings & Accessories™

### **Kuri-Clamp**™ Standard Duty Worm Gear Clamp



### **General Applications:**

- Automotive
- Industrial
- General purpose

**Construction (WGC-CS):** Four-piece construction consisting of a 1/2" wide, 300 series stainless steel band; plated carbon steel hex screw with 5/16" head and two-piece, 300 series stainless steel housing.

**Construction (WGC-SS):** Four-piece construction consisting of a 1/2" wide, 300 series stainless steel band; stainless steel hex screw with 5/16" head and two-piece, 300 series stainless steel housing.

#### **Features and Advantages:**

- Quadra-Lock Housing Four-piece, quadra-lock housing design: added saddle eliminates risk of seam separation, virtually eliminating housing "lift and twist".
- Evenly Distributed Radial Pressure Quality controlled to military standard specifications for even distribution of sealing pressure. Eliminates leakage caused by uneven housings and provides higher sealing pressure with lower applied torque.
- Arched, Perforated Slots Provides for more overall steel between perforations for added band strength and allows for smoother engagement.
- Stainless Steel Band 300 series stainless steel band provides durability and superior corrosion resistance.

to comply with military standards.

- Hex Screw Sharply defined hex angles for better gripping power. More threads per screw results in increased torque strength.
- Meets Industry Standards Clamps are SAE J1508 Type F and RoHS compliant.
- Torque Rating Suggested installation torque of 25-37 inch pounds (WGC-CS), and 30-45 inch pounds (WGC-SS).



## **Kuri-Clamp**™ Standard Duty Worm Gear Clamp

**Kuri-Clamp™ Standard Duty Worm Gear Clamp Stainless Steel Band & Housing with Carbon Steel Screw** 

**Nominal Specifications** Weight Band Torque Part Size Range Pieces Width Rating Per Box Number (in.) Per Box (in.) (in./lbs.) (lbs.) 7/16 - 25/32 1/2 WGC-CS06 10 25-37 0.60 WGC-CS08 1/2 - 29/32 10 1/2 25-37 0.60 WGC-CS10 9/16 - 1 1/16 10 1/2 25-37 0.60 WGC-CS12 10 1/2 11/16 - 1 1/4 25-37 0.60 WGC-CS16 13/16 - 1 1/2 10 1/2 25-37 0.70 WGC-CS20 13/16 - 1 3/4 10 1/2 25-37 0.70 WGC-CS24 1 1/16 - 2 10 1/2 25-37 0.80 WGC-CS28 1 5/16 - 2 1/4 10 1/2 25-37 0.80 WGC-CS32 1 9/16 - 2 1/2 10 1/2 25-37 0.80 WGC-CS36 1 13/16 - 2 3/4 10 1/2 25-37 0.90 WGC-CS40 2 1/16 - 3 10 1/2 25-37 0.90 WGC-CS44 2 5/16 - 3 1/4 10 1/2 25-37 0.90 WGC-CS48 2 9/16 - 3 1/2 10 1/2 25-37 1.00 WGC-CS52 1/2 2 13/16 - 3 3/4 10 25-37 1.10 WGC-CS56 3 1/16 - 4 10 1/2 25-37 1.10 WGC-CS60 3 5/16 - 4 1/4 10 1/2 25-37 1.20 WGC-CS64 3 9/16 - 4 1/2 10 1/2 1.20 25-37 WGC-CS72 17/8 - 5 10 1/2 25-37 1.30 WGC-CS80 2 1/2 - 5 1/2 10 1/2 25-37 1.40 10 WGC-CS88 3 1/8 - 6 1/2 25-37 1.40 1/2 WGC-CS96 3 5/8 - 6 1/2 10 25-37 1.50 4 1/8 - 7 10 WGC-CS104 1/2 25-37 1.50

**Kuri-Clamp™ Standard Duty Worm Gear Clamp** Stainless Steel Band, Housing, & Screw

Nominal Specifications					
Part Number	Size Range (in.)	Pieces Per Box	Band Width (in.)	Torque Rating (in./lbs.)	Weight Per Box (lbs.)
WGC-SS06	7/16 - 25/32	10	1/2	30-45	0.60
WGC-SS08	1/2 - 29/32	10	1/2	30-45	0.60
WGC-SS10	9/16 - 1 1/16	10	1/2	30-45	0.60
WGC-SS12	11/16 - 1 1/4	10	1/2	30-45	0.60
WGC-SS16	13/16 - 1 1/2	10	1/2	30-45	0.70
WGC-SS20	13/16 - 1 3/4	10	1/2	30-45	0.70
WGC-SS24	1 1/16 - 2	10	1/2	30-45	0.80
WGC-SS28	1 5/16 - 2 1/4	10	1/2	30-45	0.80
WGC-SS32	1 9/16 - 2 1/2	10	1/2	30-45	0.80
WGC-SS36	1 13/16 - 2 3/4	10	1/2	30-45	0.90
WGC-SS40	2 1/16 - 3	10	1/2	30-45	0.90
WGC-SS44	2 5/16 - 3 1/4	10	1/2	30-45	0.90
WGC-SS48	2 9/16 - 3 1/2	10	1/2	30-45	1.00
WGC-SS52	2 13/16 - 3 3/4	10	1/2	30-45	1.10
WGC-SS56	3 1/16 - 4	10	1/2	30-45	1.10
WGC-SS60	3 5/16 - 4 1/4	10	1/2	30-45	1.20
WGC-SS64	3 9/16 - 4 1/2	10	1/2	30-45	1.20
WGC-SS72	1 7/8 - 5	10	1/2	30-45	1.30
WGC-SS80	2 1/2 - 5 1/2	10	1/2	30-45	1.40
WGC-SS88	3 1/8 - 6	10	1/2	30-45	1.40
WGC-SS96	3 5/8 - 6 1/2	10	1/2	30-45	1.50
WGC-SS104	4 1/8 - 7	10	1/2	30-45	1.50

<sup>\*</sup> CLAMPS ONLY SOLD IN BOX QUANTITIES

<sup>\*</sup> CLAMPS ONLY SOLD IN BOX QUANTITIES