

## KC4-V450 Series

### Available Dies:

Die Number	Crimp Range (mm)	Closed Diameter (mm)	Length (mm)	Weight (lbs/ea)
KCDV119-6	6.0 - 8.0	6	60	15.4
KCDV119-8	8.0 - 10.0	8	60	15.4
KCDV119-10	10.0 - 12.0	10	60	14.4
KCDV119-12	12.0 - 14.0	12	60	14.4
KCDV119-14	14.0 - 16.0	14	60	15.5
KCDV119-16	16.0 - 19.0	16	60	15.5
KCDV119-19	19.0 - 22.0	19	60	16.6
KCDV119-22	22.0 - 25.0	22	60	16.6
KCDV119-25	25.0 - 29.0	25	60	15.5
KCDV119-29	29.0 - 34.0	29	70	15.5
KCDV119-34	34.0 - 38.0	34	70	15.5
KCDV119-38	38.0 - 42.0	38	85	15.5
KCDV119-42	42.0 - 46.0	42	85	15.5
KCDV119-46	46.0 - 50.0	46	120	19.9
KCDV119-50	50.0 - 54.0	50	120	15.5
KCDV119-54	54.0 - 58.0	54	120	16.6
KCDV119-58	58.0 - 63.0	58	120	16.6
KCDV119-63	63.0 - 69.0	63	120	17.7
KCDV119-69	69.0 - 73.0	69	120	15.5
KCDV119-73	73.0 - 77.0	73	120	13.3
KCDV119-77	77.0 - 86.0	77	120	11.1
KCDV119-86	86.0 - 90.0	86	120	12.5
KCDV119-96	96.0 - 103.0	96	120	8.9

Die Number	Crimp Range (mm)	Closed Diameter (mm)	Length (mm)	Weight (lbs/ea)
KCDV230-103	103.0 - 106.0	103	145	79.3
KCDV230-106	106.0 - 111.0	106	145	77.0
KCDV230-111	111.0 - 116.0	111	145	77.0
KCDV230-116	116.0 - 121.0	116	145	77.0
KCDV230-121	121.0 - 126.0	121	145	83.7
KCDV230-126	126.0 - 131.0	126	145	70.5
KCDV230-131	131.0 - 136.0	131	145	70.5
KCDV230-136	136.0 - 146.0	136	145	77.0
KCDV230-146	146.0 - 156.0	146	145	77.0
KCDV230-156	156.0 - 166.0	156	145	74.9
KCDV230-166	166.0 - 178.0	166	145	79.3
KCDV230-178	178.0 - 190.0	178	145	77.0
KCDV230-190	190.0 - 215.0	190	145	77.0
KCDV380-215	215.0 - 220.0	215	220	291.0
KCDV380-220	220.0 - 265.0	220	220	335.0
KCDV380-265	265.0 - 270.0	265	220	253.0
KCDV380-270	270.0 - 280.0	270	220	211.0
KCDVI01-280	280.0 - 300.0	280	220	211.0
KCDVI01-300	300.0 - 320.0	300	220	211.0
KCDVI01-320	320.0 - 340.0	320	220	211.0
KCDVI01-340	340.0 - 360.0	340	220	211.0
KCDVI01-360	360.0 - 380.0	360	220	211.0
KCDVI01-380	380.0 - 400.0	380	220	211.0

### Reduction Dies:

Die Number	Reduction Range (mm)	Weight (lbs/ea)
REDUXV1	10.0 - 96.0	155
REDUXV3	103.0 - 200.0	125

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.