

# Two-Piece Fittings - A Series



HOSES

ONE-PIECE  
B SERIES

ONE-PIECE  
D SERIES

ONE-PIECE  
F & P SERIES

TWO-PIECE FERRULES  
(A & PFR SERIES)

TWO-PIECE INSERTS  
(A SERIES)


TWO-PIECE INTERLOCK  
FERRULES & INSERTS  
(X & Z SERIES)

QUICK  
RELEASE

ASSEMBLY  
EQUIPMENT


TECHNICAL  
INFORMATION

## Inserts for two-piece fittings – International End Inserts



### Komatsu Female

Part Number	Dash Size	Hose ID Size		F Thread Size (mm) x TP (mm)	C Cut-Off Factor (mm)	Hex Dia. CH1 (mm)	Hex Dia. CH2 (mm)	Weight (lbs/each)
		(in)	(mm)					
A-0414-FKOS	04	1/4	6.4	M14x1.5	20.7	17	19	0.09
A-0618-FKOS	06	3/8	9.5	M18x1.5	22.8	19	22	0.13
A-0822-FKOS	08	1/2	12.7	M22x1.5	24.6	22	27	0.20
A-1024-FKOS	10	5/8	15.9	M24x1.5	29.2	30	32	0.40
A-1230-FKOS	12	3/4	19.0	M30x1.5	27.5	30	36	0.44
A-1633-FKOS	16	1	25.4	M33x1.5	35.7	36	41	0.77
A-2036-FKOS	20	1 1/4	31.8	M36x1.5	43.5	46	46	1.29
A-2442-FKOS	24	1 1/2	38.1	M42x1.5	44.0	55	55	1.93



### Komatsu Straight O-Ring Flange

Part Number	Dash Size	Hose ID Size		Q Flange		C Cut-Off Factor (mm)	Weight (lbs/each)
		(in)	(mm)	(in)	(mm)		
A-1010-KFLS	10	5/8	15.9	1.34	34	46.6	0.30

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

