68

TAJ5BK/BU - Alfajet 400 **Pressure Washer Hose**

Double wire braid light weight cleaning hose on easy-to-handle reels - TAJ5BK/TAJ5BU

TAJ5BK (Black) -Double wire braid



TAJ5BU (Blue) -**Double wire braid**



General Applications:

High pressure cleaning hose. For heavy duty use with hot and cold water and detergent fluids, and high pressure cleaning equipment. Extremely flexible, light weight and easy to handle. Use bend restrictors to extend service

Not recommended for steam service.

Special identification with embossed layline.

BK = Black Cover

BU = Blue Cover

Construction:

Tube - Synthetic rubber, black... hot water-

Reinforcement - Two high tensile steel wire

Cover – Pin-pricked, synthetic rubber, black or (blue, non-marking), weather, oil, ozone and abrasion resistant.

Service Temperature Range:

-40°F (-40°C) to +300°F (+155°C) constant operation.

Maximum operating temperature:

+300°F (+155°C)

Air maximum temperature: +175°F (+80°C) Note: Operating temperatures in excess of +300°F (+155°C) may materially reduce the life of the hose.

Branding - ALFAGOMMA ALFAJET 400 ID ... DN ... Bar WP - 155°C

Nominal Specifications

Series Number	Size Code	ID		OD		Max	Min. Bend. Radius			Coupling Recommendations	
		(in)	(mm)	(in)	(mm)	Working† Pressure (psi)	(in)	(mm)	Weight (lbs/ft)	Alfacrimp	Two-Piece
										One-Piece	Ferrule Non-Skive
TAJ5BK	04	1/4	6.4	0.52	13.2	5850	2.7	68.6	0.18	В	AF1
TAJ5BK	05	5/16	7.9	0.59	14.9	5850	3.0	762	0.20	В	AF1
TAJ5BK	06	3/8	9.5	0.66	16.7	5850	3.5	88.9	0.26	В	AF1
TAJ5BK	- 08	1/2	12.7	0.79	20.1	5850	4.5	114.3	0.34	В	AF1
TAJ5BU	04	1/4	6.4	0.52	13.2	5850	2.7	68.6	0.18	В	AF1
TAJ5BU	05	5/16	7.9	0.59	14.9	5850	3.0	762	0.20	В	AF1
TAJ5BU	06	3/8	9.5	0.66	16.7	5850	3.5	88.9	0.26	В	AF1
TAJ5BU	80	1/2	12.7	0.79	20.1	5850	4.5	114.3	0.34	В	AF1

[†] Minimum burst pressure 4-to-1 safety factor.

Freight: Hydraulic Hose can be combined with other KOA products for qualifying prepaid freight orders.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

