

# WB20 - Waterblast MINETUFF



HOSES  
ONE-PIECE B SERIES  
ONE-PIECE D SERIES  
ONE-PIECE F & P SERIES  
TWO-PIECE FERRULES (A & PFR SERIES)  
TWO-PIECE INSERTS (A SERIES)  
TWO-PIECE INTERLOCK FERRULES & INSERTS (X & Z SERIES)  
QUICK RELEASE  
ASSEMBLY EQUIPMENT  
TECHNICAL INFORMATION

## Waterblast Hose WB 20

**NEW**

**WB20 –  
4 wire spiral**



### General Applications:

High pressure water jetting

### Construction:

**Tube** – Oil and water resistant synthetic rubber.

**Reinforcement** – Four high tensile steel spirals and one steel braid.

**Cover** – Oil, water and ozone resistant synthetic rubber.

### Service Temperature Range:

Constant operation: +14°F (-10°C) to +158°F (+70°C)

### Branding:

Dunlop Hiflex

### Length:

Random length coils, all in multiples of 50 feet.

Examples: 200', 250', 300', 350'

## Nominal Specifications

Series Number	Size Code	ID		OD		Max Working† Pressure (psi)	Min. Bend. Radius		Weight (lbs/ft)	Coupling Recommendations
		(in)	(mm)	(in)	(mm)		(in)	(mm)		Two-Piece Ferrule Interlock
WB20	04	1/4	6.0	0.64	16.2	20000	4.92	125	0.41	WF9
WB20	06	3/8	10.0	0.87	22.0	20000	5.91	150	0.69	WF8
WB20	08	1/2	13.0	1.16	29.5	20000	7.87	200	0.97	WF8
WB20	12	3/4	19.0	1.38	35.0	20000	11.81	300	1.70	WF8

† Minimum burst pressure: 2.5-to-1 safety factor.

**Freight:** Hydraulic Hose can be combined with other KOA products for qualifying prepaid freight orders.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

