Kuri Tec[®]

PNEU-THANE™ HS5090, HS5094, HS5096 Series



Lightweight Reinforced

Polyurethane Pneumatic Air Tool Hose Assemblies

(with Rubber Bend Restrictors)

Service Temperature Range: -40°F (-40°C) to +185°F (+85°C)

| | Nominal Specifications | | | | | | | | | | | | |
|---|------------------------|---------------------------|------------|------|---------|------------|------|------------------------------------|------------------|---------------|-------------------------------------|--------|---------|
| | Standard Stock Colors | | Nominal ID | | inal ID | Nominal OD | | Maximum Working Pressure† (PSI) | | Assembled | Approx. Wt. per Pkg | | |
| | HS5090 Aqua | HS5094 Red HS5096 Blue | Code | (ln) | (mm) | (ln) | (mm) | @70°F (20°C) | @122°F (50°C) | Lengths | 25 ft. | 50 ft. | 100 ft. |
| Ī | V | V | 04 | 1/4 | 6.5 | .395 | 10.0 | 250 | 200 | 25/50/100 ft. | 1 lbs. | 2 lbs. | 4 lbs. |
| ١ | ~ | / | 06 | 3/8 | 9.5 | .560 | 14.2 | 250 | 200 | 25/50/100 ft. | 1.5 lbs. | 3 lbs. | 6 lbs, |

Note: Hose assemblies are furnished with the following fittings: 1/4" ID - 1/4" X 1/4"M NPT, 3/8" ID - 3/8" X 1/4"M NPT.

Note: Refer to page 28 for Technical Information.

TUNDRA-AIR® HS1231, HS1234, HS1236 Series

High Grade Low Temperature Air Hose Assemblies

(with Rubber Bend Restrictors)

1/4" and 3/8" sizes only.



Service Temperature Range: -65°F (-54°C) to +150°F (+65°C)

Nominal Specifications

| Standard Stock Colors | | | Size | Nominal ID | | Nominal OD | | Maximum Working Pressure† (PSI) | | Assembled | Approx. Wt. per Pkg. | | |
|--------------------------|-----------------|----------------|----------------|-------------------|--------------------|----------------------|----------------------|------------------------------------|-------------------|---|----------------------------------|--------|------------------------------------|
| HS1231 Yellow | HS1234 Red | HS1236 Blue | Code | (ln) | (mm) | (ln) | (mm) | @70°F (20°C) | @122°F (50°C) | Lengths | 25 ft. | 50 ft. | 100 ft. |
| \ \ \ \ | \(\frac{1}{2}\) | V V | 04 06 08 | 1/4 3/8 1/2 | 6.5 9.5 12.7 | .500 .625 .781 | 12.7 15.9 19.8 | 300 300 300 | 160 160 160 | 25/50/100 ft. 25/50/100 ft. 25/50/100 ft. | 2.0 lbs. 2.8 lbs. 4.1 lbs. | | 7.8 lbs. 10.7 lbs. 16.0 lbs. |

† Note: Working Pressure decreases as temperature increases. Pressure ratings can only be obtained with proper coupling procedures.

Note: Hose assemblies are furnished with the following fittings: 1/4" ID - 1/4" X 1/4" M NPT, 3/8" ID - 3/8" X 1/4" M NPT, 1/2" ID - 1/2" X 3/8" M NPT.

Note: Refer to page 30 for Technical Information.

NOTE: For details of the following compliances mentioned above, refer to footnotes listed on page 63.

PHTHALATE FREE (15)

Please refer to the back page for the location of your nearest warehouse for availability of products/sizes shown.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.

KKTCA0617 39