57

Kuri Tec[®]

A4176 Series **Conductive PVC Air Hose with Polyurethane Cover**



Uniquely different PVC air hose that prevents static build-up without the need of a static wire.

Construction:

- Tube Co-extruded electrically-conductive PVC.
- Reinforcement Spiral polyester yarn.
- Cover Blue polyurethane for superior abrasion resistance.

Features:

- Continuous flexible conductive liner assures contact with fittings, without special preparation or clamping techniques.
- No wires to break when the hose is flexed.
- Distinctive color and branding allows easy identification.
- Silicone-free.
- One-piece lengths.
- Branded as "Conductive Air".

- Excellent chemical and abrasion resistance afforded by polyurethane cover.
- Non-marking non-perforated cover.
- Phthalate Free!

Applications:

- In-plant air service where static dissipation is required.
- Air lines for painting equipment.
- Applications requiring the use of grounded pneumatic tools.

Electrical Data:

- Resistance is less than 100,000 ohms per foot when tested with an ohmmeter, with normal open-circuit output voltage of 500 VDC.
- Note: Conductivity is through the inner liner only. To dissipate static electricity, the hose must be fitted with a grounded conductive coupling. When measured through the wall of the hose, the product demonstrates electrical insulation.

Service Temperature Range: +14° F (-10° C) to +150° F (+65° C)

Nominal Specifications											
Series No.	Size Code	Nominal ID		Nominal OD		Max. Working Pressure† (PSI)		Standard Length Coils		Approx. Wt. per Pkg.	
		(ln)	(mm)	(ln)	(mm)	@ 70°F (20°C)	@ 122°F (50°C)	Reel	Coil	Reel	Coil
A4176 * A4176 A4176	04 06 08	1/4 3/8 1/2	6.5 9.5 12.7	.500 .625 .813	12.7 15.9 20.7	300 300 300	180 180 180	500 ft. 500 ft. 500 ft.	100 ft. 100 ft. 100 ft.	44 lbs. 58 lbs. 93 lbs.	8 lbs. 11 lbs. 18 lbs.

[†] Note: Working Pressure decreases as temperature increases. Pressure ratings can only be obtained with proper coupling procedures.

NOTE: For details of the following compliances mentioned above, refer to footnotes listed on page 63.

PHTHALATE FREE⁽¹⁵⁾

Please refer to the back page for the location of your nearest warehouse for availability of products/sizes shown.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS. WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.

^{*}Non stock item.