

## Alfabiotech 2000 MINETUFF - ABT2K Hydraulic Hose



### ABT2K- 4 Spirals

MSHA IC-152/16 approved flame resistance

ISO 18752/CC 1,000,000+ impulse cycles all sizes



### General Applications:

Developed to withstand very demanding conditions very high performance in pressure, pulsing and flexing.

### Construction:

**Tube** – Oil resistant synthetic rubber and biodegradable hydraulic fluids.

**Reinforcement** – Four high tensile steel spirals.

**Cover** – Abrasion, ozone and hydrocarbon resistant synthetic rubber.

### Service Temperature Range:

-40°F (-40°C) to +250°F (+121°C)

### Branding:

Alfagomma Alfabiotech 2K Minetuff 2000 PSI Hydraulic Service - 3200 PSI Slim Hole Rotary Service MSHA IC-152/16 Made in Italy

### Length:

100 feet. 200 foot lengths available upon request.

## Nominal Specifications

Series Number	Size Code	ID		OD		Max Working <sup>†</sup> Pressure (psi)	Min. Bend. Radius		Weight (lbs/ft)	Coupling Recommendations	
		(in)	(mm)	(in)	(mm)		(in)	(mm)		Two-Piece	
										Ferrule Skive	Ferrule Interlock
ABT2K	40	2 1/2	63.5	3.11	79.0	2000*	28.3	718.8	3.33	VS4	XF1
ABT2K	48	3	76.2	3.64	92.5	2000*	33.0	838.2	3.64	VS4	

\*Note: Slim Hole Rotary Hose Working Pressure 3200 psi, Hydraulic Service 2000 psi.

† Minimum burst pressure 4-to-1 hydraulic service/2.5-to-1 slim hole rotary.

**Freight:** Hydraulic Hose can be combined with other KOA products for qualifying prepaid freight orders.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.