




IM-75 Series *(Fluoroelastomer – FKM)*

Black Sheet

GENERAL PROPERTIES

- Excellent sealing capability in aggressive environments
- Excellent chemical resistance
- UV & ozone resistant
- Resistant to liquid permeation in severe conditions
- Cinnamon scented for easy identification

POLYMER

Fluoroelastomer (FKM)

View Up To Date Info



◀ SCAN OR VISIT
KOA.link/IM-75

Series	ASTM Specification (SI units)	Temperature Range	Durometer	Tensile Strength (psi)	Elongation (%)
IM-75	ASTM D2240	-20° to 450°F (-29° to 232°C)	75 +/- 5	1000 min.	225 min.

ADDITIONAL SPECIFICATIONS

Grade	Industrial
Finish	Smooth
Powder	No
Color	Black

Item Number	Gauge x Width (in)	Avg. Length (Linear Ft./Roll)	Surface (sft)	Approx. Lbs./Roll
350-04-482	1/16 x 48	50	200	150
350-08-482	1/8 x 48	51	204	286
350-12-482	3/16 x 48	20	80	152
350-16-482	1/4 x 48	20	80	202

Material is within commercial sheet rubber gauge tolerances.
The documentation for sheet rubber gauge tolerances is published on our website.
Please ensure the product meets your application specification prior to order placement.
Specifications are subject to change without notice. The website version prevails.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.