



IM-619 Series *(Styrene-Butadiene)*

Fabric Finish Red Sheet

GENERAL PROPERTIES

- Industrial SBR for gaskets

POLYMER

Styrene-Butadiene (SBR)

View Up To Date Info



◀ SCAN OR VISIT
[KOA.link/
IM-619](https://KOA.link/IM-619)

Series	ASTM Specification (SI units)	Temperature Range	Durometer	Tensile Strength (psi)	Elongation (%)
IM-619	ASTM D2240	-20° to 180°F (-29° to 82°C)	75 +/- 7	400 typical	220 typical

ADDITIONAL SPECIFICATIONS

Grade	Industrial
Finish	Fabric
Powder	No
Color	Red

Item Number	Gauge x Width (in)	Avg. Length (Linear Ft. /Roll)	Surface (sft)	Approx. Lbs./Roll
111-04-368	1/16 x 36	70	210	119
111-04-488	1/16 x 48	50	200	113
111-08-368	1/8 x 36	35	105	119
111-08-488	1/8 x 48	25	100	113
111-12-368	3/16 x 36	50	150	254
111-16-368	1/4 x 36	35	105	237
111-16-488	1/4 x 48	25	100	226

Maximum pieces per roll: 2 • Minimum piece length: 5' • Width tolerance: -0.5 / +1"

Material is within commercial sheet rubber gauge tolerances.

The documentation for sheet rubber gauge tolerances is published on our website.

Please ensure the product meets your application specification prior to order placement.

Specifications are subject to change without notice. The website version prevails.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.