



AB-135 Series *(Natural Rubber)*

Tan Premium Sheet

GENERAL PROPERTIES

- Superior tensile strength for demanding applications
- Cut, tear and abrasion resistant
- Rebound elasticity (snap)
- Flexibility
- Good adhesion with proper surface prep

View Up To Date Info



◀ SCAN OR VISIT
KOA.link/AB-135

POLYMER

Natural Rubber (NR)

Series	ASTM Specification (SI units)	Temperature Range	Durometer	Tensile Strength (psi)	Elongation (%)
AB-135	D2000: 2AA425A13F17	-20° to 180°F (-29° to 82°C)	40	2500 min.	400 min.

ASTM D2000 SPECIFICATION AND TESTS

	ASTM	Description	Value
	DIN	Abrasion Method 53516	Wet: 39 mm3 Dry: 176 mm3
	D2137	Cold Temperature	-40°C/°F min.
	D395 (Method B)	Compression Set 22 hrs @ 70°C (158°F)	50% max.
	D573	Heat Aging 70 hrs @ 70°C (158°F)	Hardness: +/-15 Tensile (%): +/-30 max. Elongation (%): -50 max.

ADDITIONAL SPECIFICATIONS

Grade	Premium
Finish	Smooth
Powder	Yes
Color	Tan

Item Number	Gauge x Width (in)	Avg. Length (Linear Ft. /Roll)	Surface (sft)	Approx. Lbs./Roll
127-04-362*	1/16 x 36	100	300	97
127-04-482*	1/16 x 48	100	400	130
127-06-482*	3/32 x 48	75	300	152
127-08-362	1/8 x 36	50	150	108
127-08-482	1/8 x 48	50	200	144
127-12-362*	3/16 x 36	40	120	123

continued

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.



AB-135 Series *(Natural Rubber)*

Tan Premium Sheet

continued from page 6

Item Number	Gauge x Width (in)	Avg. Length (Linear Ft. /Roll)	Surface (sft)	Approx. Lbs./Roll
127-12-482	3/16 x 48	40	160	164
127-16-362	1/4 x 36	40	120	164
127-16-482	1/4 x 48	40	160	219
127-24-362*	3/8 x 36	30	90	183
127-24-482	3/8 x 48	30	120	243
127-32-362	1/2 x 36	50	150	407
127-32-482	1/2 x 48	50	200	542
127-48-362*	3/4 x 36	30	90	361
127-48-488*	3/4 x 48	30	120	481
127-64-368	1 x 36	30	90	486

*Non-stocked size. Made to order with required number of rolls. Longer lead time applies. Contact Kuriyama Customer Service for details.
Maximum pieces per roll: 2 • Minimum piece length: 10' • Width tolerance: -0 / +1"
Material is within commercial sheet rubber gauge tolerances.
The documentation for sheet rubber gauge tolerances is published on our website.
Please ensure the product meets your application specification prior to order placement.
The website version prevails.
Total roll length may vary by ±10% for domestically manufactured (AB-135) Series.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.