



T202AA EVOLUTION Series

150 PSI EPDM General Purpose Water S & D Hose

GENERAL APPLICATIONS

- Construction
- Fertilizers
- Irrigation lines
- Lasso acid solutions
- Suction and discharge
- Non-corrosive liquids

CONSTRUCTION

Tube - Black EPDM
Reinforcement - Spiraled high tensile textile spiral cords with flexible steel helix wire
Cover - Black EPDM – abrasion, ozone, and UV resistant

WORKING PRESSURE

Constant Pressure – 10 Bar (150 PSI)

SERVICE TEMPERATURE RANGE

-40°F (-40°C) to +212°F (+100°C)*
**Actual service temperature range is application dependent.*

BRANDING

Alfagomma – Italy – 202 EVOLUTION 10 BAR (150 PSI) GENERAL PURPOSE EPDM (in green letters)

View Up To Date Info



◀ SCAN OR VISIT
[KOA.link/
T202AA](https://KOA.link/T202AA)



FOR APPLICATIONS INVOLVING
INDUSTRIAL ACID CHEMICALS AND
ALCOHOLS, PLEASE REFER TO
T5050G AND T5090E HOSES

Series Number	ID		OD		Max. Working Pressure (psi)	Vacuum Rating Hg (in)	Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)					
T202AA100	1	25	1.42	36	150	30	2	100	0.48
T202AA125	1 1/4	32	1.69	43	150	30	2 1/2	100	0.58
T202AA150	1 1/2	38	1.93	49	150	30	3	100	0.68
T202AA200	2	51	2.44	62	150	30	4	100	0.88
T202AA250	2 1/2	63	2.99	76	150	30	7 1/2	100	1.36
T202AA300	3	76	3.50	89	150	30	9	100	1.61
T202AA350	3 1/2	90	4.02	102	150	30	10 1/2	100	1.82
T202AA400	4	102	4.57	116	150	30	12	100	2.22
T202AA500	5	127	5.55	141	150	25	18	20/50	3.18
T202AA600	6	152	6.61	168	150	25	24	20/25/50/100	3.59
T202AA800	8	203	8.70	221	150	25	32	20/25	6.64
T202AA1000	10	254	10.71	272	150	25	50	20	9.09
T202AA1200	12	305	12.87	327	150	25	61	20	12.54

COUPLING SUGGESTIONS: Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.



Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.