

T223AA Series

300 PSI EPDM Heavy Duty S & D Hose

View Up To Date Info

SCAN OR VISIT
KOA.link/
T223AA

FOR APPLICATIONS INVOLVING INDUSTRIAL ACID CHEMICALS AND ALCOHOLS, PLEASE REFER TO T5050G AND T5090E HOSES

GENERAL APPLICATIONS

- Designed for long service life in heavy duty applications for water suction and delivery service
- Heavy duty water suction and discharge applications for irrigation, agriculture, mining and construction

CONSTRUCTION

Tube - Black conductive EPDM

Reinforcement - Spiraled high tensile textile cords with flexible steel helix wire

Cover - Black conductive EPDM – abrasion and ozone resistant

WORKING PRESSURE

Constant Pressure – 20 Bar (300 PSI)

SERVICE TEMPERATURE RANGE

-40°F (-40°C) to +212°F (+100°C)

BRANDING

ALFAGOMMA-ITALY-223 20 BAR (300 PSI) WATER S & D (in green letters)

Series Number	ID (in)	ID (mm)	OD (in)	OD (mm)	Max. Working Pressure (psi)	Vacuum Rating Hg (in)	Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
T223AA200	2	51	2.48	63	300	30	8	100	0.96
T223AA250	2 1/2	63	3.03	77	300	27	10	100	1.40
T223AA300	3	76	3.54	90	300	27	12	100	1.72
T223AA400	4	102	4.57	116	300	27	16	100	2.35
T223AA600	6	152	6.61	168	300	24	24	100	4.58
T223AA800	8	203	8.86	225	300	21	32	40	7.34

COUPLING SUGGESTIONS: Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.