



T351LL / T351LG Series*

150 PSI EPDM Premium Paper Mill/Creamery Wash Down Hose with Tapered Nozzle

GENERAL APPLICATIONS

- For general wash down service, using hot and cold water in paper mills and in food and dairy plants

CONSTRUCTION

Tube – White EPDM. Meets FDA and 3A (18-03) requirements
Reinforcement – Two ply, high tensile textile cords
Cover – White or green EPDM – heat, abrasion and ozone resistant

WORKING PRESSURE

Constant Pressure – 10 Bar (150 PSI)

SERVICE TEMPERATURE RANGE

-40°F (-40°C) to +248°F (+120°C)

STANDARD LENGTH

50 feet including 6" long built-in tapered nozzle*

***TAPERED NOZZLE HOLE SIZE**

3/4" and 1" ID....3/8"
1 1/4" ID.....1/2"
1 1/2" ID.....5/8"

View Up To Date Info



◀ SCAN OR VISIT
**KOA.link/
T351LL-LG**



Series Number	ID		OD		Max. Working Pressure (psi)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)			
T351LL/LG075	3/4	19	1.22	31	150	50	0.44
T351LL/LG100	1	25	1.46	37	150	50	0.54
T351LL/LG125	1 1/4	32	1.81	46	150	50	0.78
T351LL/LG150	1 1/2	38	2.05	52	150	50	0.91

*T351 fully complies with the requirements listed in FDA CFR21.

COUPLING SUGGESTIONS: Short shank, long shank couplings (NPT, GHT), barbed inserts attached with bands.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.