



View Up To Date Info



◀ SCAN OR VISIT
**KOA.link/
T146AK**

T146AK Series

1000 PSI Braided MSHA Mine Spray Hose

GENERAL APPLICATIONS

- Underground mine water spray for dust control
- Usable on continuous mining machinery

CONSTRUCTION

Tube – Black Extruded SBR/NBR blend – oil mist resistant
Reinforcement – High tensile steel wire braids
Cover – Yellow SBR/NBR blend – abrasion, ozone, hydrocarbon and fire resistant – pin pricked

WORKING PRESSURE

Constant Pressure – 70 BAR (1000 PSI)

SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +200°F (+90°C)

BRANDING

ALFAGOMMA – ITALY -146 – 70 BAR (1000 PSI) MINE SPRAY MSHA IC – 152/6 (embossed)

Series Number	ID		OD		Max. Working Pressure (psi)	Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)				
T146AK075	3/4	19	1.10	28	1000	3 3/4	50/100	0.45
T146AK100	1	25	1.34	34	1000	5	50/100	0.58
T146AK125	1 1/4	32	1.61	41	1000	6 1/4	50/100	0.75
T146AK150	1 1/2	38	1.93	49	1000	7 1/2	50/100	1.08
T146AK200	2	51	2.48	63	1000	10	50/100	1.47

COUPLING SUGGESTIONS: Permanently attached crimped hydraulic couplings.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.