



View Up To Date Info



◀ SCAN OR VISIT
**KOA.link/
T352AA**

T352AA Series

75 PSI Radiator Hose

GENERAL APPLICATIONS

- Radiator hose

CONSTRUCTION

Tube – Black EPDM
Reinforcement – Two ply, high tensile textile cords – 2 ply all sizes. Not for vacuum
Cover – Black EPDM – heat, abrasion and ozone resistant

WORKING PRESSURE

Constant Pressure –
5 Bar (75 PSI)

SERVICE TEMPERATURE RANGE

-40°F (-40°C) to +248°F (+120°C)

BRANDING

ALFAGOMMA – ITALY – 352 RADIATOR – DIN 73411 – dia mm / in. SAE 20R1-D2 (in yellow letters)

Series Number	ID		OD		Max. Working Pressure (psi)	Standard Length Coils (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)			
T352AA050X12.6	1/2	13	0.83	21	75	12'6"	0.19
T352AA050X200	1/2	13	0.83	21	75	200'	0.19
T352AA062X12.6	5/8	16	0.94	24	75	12'6"	0.22
T352AA071X12.6	23/32	18	1.02	26	75	12'6"	0.24
T352AA078X12.6	13/16	20	1.10	28	75	12'6"	0.26
T352AA087X12.6	7/8	22	1.18	30	75	12'6"	0.28
T352AA087X200	7/8	22	1.18	30	75	200'	0.28
T352AA100X12.6	1	25	1.30	33	75	12'6"	0.32
T352AA100X200	1	25	1.30	33	75	200'	0.32
T352AA112X12.6	1 1/8	28	1.42	36	75	12'6"	0.34
T352AA112X200	1 1/8	28	1.42	36	75	200'	0.34
T352AA118X12.6	1 3/16	30	1.50	38	75	12'6"	0.37
T352AA125X12.6	1 1/4	32	1.57	40	75	12'6"	0.39
T352AA125X200	1 1/4	32	1.57	40	75	200'	0.39

See additional sizes...

Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.



T352AA Series
75 PSI Radiator Hose

(continued from previous page)

View Up To Date Info



◀ SCAN OR VISIT
**KOA.link/
T352AA**

Series Number	ID		OD		Max. Working Pressure (psi)	Standard Length Coils (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)			
T352AA137X12.6	1 3/8	35	1.69	43	75	12'6"	0.42
T352AA150X12.6	1 1/2	38	1.89	48	75	12'6"	0.57
T352AA150X200	1 1/2	38	1.89	48	75	200'	0.57
T352AA162X12.6	1 5/8	42	2.05	52	75	12'6"	0.63
T352AA162X200	1 5/8	42	2.05	52	75	200'	0.63
T352AA175X12.6	1 3/4	45	2.17	55	75	12'6"	0.66
T352AA175X200	1 3/4	45	2.17	55	75	200'	0.66
T352AA189X12.6	1 7/8	48	2.28	58	75	12'6"	0.70
T352AA189X200	1 7/8	48	2.28	58	75	200'	0.70
T352AA200X12.6	2	51	2.40	61	75	12'6"	0.75
T352AA200X200	2	51	2.40	61	75	200'	0.75
T352AA225X12.6	2 1/4	57	2.64	67	75	12'6"	0.82
T352AA238X12.6	2 3/8	60	2.76	70	75	12'6"	0.86
T352AA250X12.6	2 1/2	63	2.87	73	75	12'6"	0.90
T352AA275X12.6	2 3/4	70	3.15	80	75	12'6"	0.97
T352AA300X12.6	3	76	3.39	86	75	12'6"	1.04
T352AA315X12.6	3 1/8	80	3.54	90	75	12'6"	1.10
T352AA354X12.6	3 9/16	90	4.02	102	75	12'6"	1.36
T352AA400X12.6	4	102	4.49	114	75	12'6"	1.52
T352AA450X12.6	4 1/2	116	5.00	127	75	12'6"	1.69
T352AA500X12.6	5	127	5.55	141	75	12'6"	2.16

Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.