



T155AK Series

300 PSI Textile Cord "Air Drill" Hose

GENERAL APPLICATIONS

- High quality air hose for mining and construction service
- Can be used for water

CONSTRUCTION

Tube – Black non-conductive SBR/NBR blend – oil mist resistant

Reinforcement – Spiraled, high tensile textile cords

Cover – Yellow non-conductive SBR – abrasion and ozone-resistant

View Up To Date Info



◀ SCAN OR VISIT
[KOA.link/
T155AK](https://KOA.link/T155AK)

WORKING PRESSURE

Constant Pressure –
20 Bar (300 PSI)

SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +176°F (+80°C)

BRANDING

ALFAGOMMA – ITALY – 155 20 BAR (300 PSI) AIR (in blue letters).

Series Number	ID		OD		Max. Working Pressure (psi)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)			
T155AK050	1/2	13	0.83	21	300	50/100	0.22
T155AK075	3/4	19	1.14	29	300	100	0.38
T155AK100	1	25	1.38	35	300	50/100	0.48
T155AK125	1 1/4	32	1.73	44	300	100	0.60
T155AK150	1 1/2	38	1.97	50	300	100	0.70
T155AK200	2	51	2.56	65	300	50/100	1.12
T155AK250	2 1/2	63	3.11	79	300	50/100	1.55
T155AK300	3	76	3.62	92	300	50/100	1.89
T155AK400	4	102	4.65	118	300	50/100	2.47

COUPLING SUGGESTIONS: Steel or malleable iron male insert NPT, female ground joint or washer type with spud, attached with 2 or 4 bolt interlocking clamps or bands. Universal couplings may be used on sizes (1/2" – 2")



Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.