



## T902AA Series

### 150 PSI High Quality Hot Air Blower Hose

#### GENERAL APPLICATIONS

- Hot air transfer between the air compressor and dry bulk tank on bulk material carriers

#### CONSTRUCTION

**Tube** – Black EPDM – heat-resistant  
**Reinforcement** – Spiraled high tensile textile cords with flexible steel helix wire  
**Cover** – Black EPDM – heat, abrasion and ozone resistant

#### WORKING PRESSURE

Constant Pressure –  
 10 Bar (150 PSI)

#### SERVICE TEMPERATURE RANGE

-40°F (-40°C) to +356°F (+180°C)

#### BRANDING

ALFAGOMMA – ITALY – 902 10 BAR (150 PSI) – HOT AIR SERVICE (in white letters)

View Up To Date Info



◀ SCAN OR VISIT  
[KOA.link/T902AA](https://KOA.link/T902AA)

Series Number	ID		OD		Max. Working Pressure (psi)	Vacuum Rating Hg (in)	Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)					
T902AA200	2	51	2.48	63	150	30	6	100	1.01
T902AA300	3	76	3.54	90	150	27	9	100	1.60
T902AA400	4	102	4.57	116	150	27	12	100	2.23

**COUPLING SUGGESTIONS:** Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

**i** Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – [KOA.link/KOA-Couplings-Catalog](https://KOA.link/KOA-Couplings-Catalog)

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.