



## T903LE Series

### 150 PSI High Quality FDA Hot Air Blower Hose

#### GENERAL APPLICATIONS

- Hot air transfer between the air compressor and dry bulk tank on bulk material carriers

#### CONSTRUCTION

**Tube** – White EPDM – heat-resistant. Meets FDA requirements

**Reinforcement** – Spiraled high tensile textile cords with flexible steel helix wire

**Cover** – Blue EPDM – heat, abrasion and ozone resistant

#### WORKING PRESSURE

Constant Pressure –  
10 Bar (150 PSI)

#### SERVICE TEMPERATURE RANGE

-40°F (-40°C) to +356°F (+180°C)

#### BRANDING

ALFAGOMMA – ITALY – 903 10 BAR (150 PSI) – HOT AIR SERVICE – FDA (in white letters)

View Up To Date Info



◀ SCAN OR VISIT

[KOA.link/  
T903LE](https://KOA.link/T903LE)

Series Number	ID		OD		Max. Working Pressure (psi)	Vacuum Rating Hg (in)	Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)					
T903LE300	3	76	3.54	90	150	27	9	100	1.65
T903LE400	4	102	4.57	116	150	27	12	100	2.26

**COUPLING SUGGESTIONS:** Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.



Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – [KOA.link/KOA-Couplings-Catalog](https://KOA.link/KOA-Couplings-Catalog)

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.