



T223AA 300 PSI EPDM

Heavy Duty S & D Hose

GENERAL APPLICATIONS

- Designed for long service life in heavy duty applications for water suction and delivery service
- Heavy duty water suction and discharge applications for irrigation, agriculture, mining and construction

CONSTRUCTION

Tube - Black conductive EPDM

Reinforcement - Spiraled high tensile textile cords with flexible steel helix wire

Cover - Black conductive EPDM – abrasion and ozone resistant

WORKING PRESSURE

Constant Pressure – 20 Bar (300 PSI)

SERVICE TEMPERATURE RANGE

-40°F (-40°C) to +212°F (+100°C)

BRANDING

ALFAGOMMA-ITALY-223 20 BAR (300 PSI) WATER S & D (in green letters)

View Up To Date Info



← SCAN OR VISIT
[KOA.link/
T223AA](https://KOA.link/T223AA)

! FOR APPLICATIONS INVOLVING INDUSTRIAL ACID CHEMICALS AND ALCOHOLS, PLEASE REFER TO T5050G AND T5090E HOSES

Series Number	ID		OD		Max. Working Pressure (psi)	Vacuum Rating Hg (in)	Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)					
T223AA200	2	51	2.48	63	300	30	8	100	0.96
T223AA250	2 1/2	63	3.03	77	300	27	10	100	1.40
T223AA300	3	76	3.54	90	300	27	12	100	1.72
T223AA400	4	102	4.57	116	300	27	16	100	2.35
T223AA600	6	152	6.61	168	300	24	24	100	4.58
T223AA800	8	203	8.86	225	300	21	32	40	7.34

COUPLING SUGGESTIONS: Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.



Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.