



T204AA Series

75 PSI SBR Water S & D Hose

GENERAL APPLICATIONS

- Suction and discharge of water for irrigation and construction

CONSTRUCTION

Tube – Black SBR

Reinforcement – Spiraled high tensile textile cords with flexible steel helix wire

Cover – Black SBR – ozone and abrasion-resistant

WORKING PRESSURE

Constant Pressure –
5 Bar (75 PSI)

SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +176°F (+80°C)

BRANDING

ALFAGOMMA – ITALY – 204 (embossed)

View Up To Date Info



◀ SCAN OR VISIT
[KOA.link/
T204AA](https://KOA.link/T204AA)

Series Number	ID		OD		Max. Working Pressure (psi)	Vacuum Rating Hg (in)	Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)					
T204AA600	6	152	6.54	166	75	24	30	20/25/50/100	4.13
T204AA800	8	203	8.70	221	75	21	40	20/25	7.06

COUPLING SUGGESTIONS: Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

i Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.