



T254AA Series

150 PSI SBR Water Discharge Hose

GENERAL APPLICATIONS

- Water discharge hose for construction and irrigation

CONSTRUCTION

Tube – Black SBR

Reinforcement – High tensile textile cords – 2 spirals up to 4", 4 spirals above 4"

Cover – Black SBR – abrasion and ozone-resistant

WORKING PRESSURE

Constant Pressure –
10 Bar (150 PSI)

SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +176°F (+80°C)

BRANDING

ALFAGOMMA – ITALY – 10 BAR (150 PSI) AIR & WATER (in green letters)

FEATURES AND ADVANTAGES

- SBR Has better abrasion resistance than EPDM.
- Superior tear strength and low temperature flexibility.

View Up To Date Info



◀ SCAN OR VISIT

[KOA.link/
T254AA](https://KOA.link/T254AA)

Series Number	ID		OD		Max. Working Pressure (psi)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)			
T254AA150	1 1/2	38	1.89	48	150	100	0.66
T254AA200	2	51	2.40	61	150	100	0.87
T254AA300	3	76	3.46	88	150	100	1.54
T254AA400	4	102	4.49	114	150	100	2.08
T254AA600	6	152	6.54	166	150	100	3.13
T254AA800	8	203	8.62	219	150	50/100	4.64

COUPLING SUGGESTIONS: Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

i Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.