



T350LL
White Cover



T350LH
Red Cover

T350LL / T350LH Series*

225 PSI Premium Paper Mill/Creamery Wash Down
Hose – No Nozzle

GENERAL APPLICATIONS

- For general wash down service, using hot water or low pressure saturated steam in processing plants and facilities and in food and dairy plants

CONSTRUCTION

Tube – White EPDM. Meets FDA and 3A (18-03) requirements

Reinforcement – High tensile textile cords

Cover – Red or white EPDM – heat, abrasion and ozone resistant

WORKING PRESSURE

Constant Pressure – 15 Bar (225 PSI)

STEAM PRESSURE

Constant Pressure – 6 Bar (90 PSI)

SERVICE TEMPERATURE RANGE

Water -40°F (-40°C) to +248°F (+120°C)

Steam +330°F to (+165°C)

View Up To Date Info



◀ SCAN OR VISIT
**KOA.link/
T350LL-LH**

BRANDING

ALFAGOMMA – ITALY – 350 6 BAR (90 PSI) STEAM 15 BAR (225 PSI) HOT WATER (embossed)

STANDARD LENGTH

200 feet – eliminates bulky hookups



Series Number	ID		OD		Max. Working Pressure (psi)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)			
T350LL050	1/2	13	0.91	23	225	200	0.27
T350LL062	5/8	16	1.02	26	225	200	0.31
T350LL/LH075	3/4	19	1.22	31	225	200	0.44
T350LL/LH100	1	25	1.46	37	225	200	0.54
T350LL125	1 1/4	32	1.81	46	225	200	0.63
T350LL150	1 1/2	38	2.05	52	225	200	0.74
T350LL200	2	51	2.64	67	225	200	1.12

*T350 fully complies with the requirements listed in FDA CFR21.

COUPLING SUGGESTIONS: Short shank, long shank couplings (NPT, GHT), barbed inserts attached with bands.



Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.