



T351LL
White Cover



T351LG
Green Cover

T351LL / T351LG Series*

150 PSI EPDM Premium Paper Mill/Creamery Wash Down Hose with Tapered Nozzle

GENERAL APPLICATIONS

- For general wash down service, using hot and cold water in paper mills and in food and dairy plants

CONSTRUCTION

Tube – White EPDM. Meets FDA and 3A (18-03) requirements

Reinforcement – Two ply, high tensile textile cords

Cover – White or green EPDM – heat, abrasion and ozone resistant

WORKING PRESSURE

Constant Pressure – 10 Bar (150 PSI)

SERVICE TEMPERATURE RANGE

-40°F (-40°C) to +248°F (+120°C)

STANDARD LENGTH

50 feet including 6" long built-in tapered nozzle*

*TAPERED NOZZLE HOLE SIZE

3/4" and 1" ID....3/8"

1 1/4" ID.....1/2"

1 1/2" ID.....5/8"

View Up To Date Info



◀ SCAN OR VISIT

KOA.link/

T351LL-LG



Series Number	ID		OD		Max. Working Pressure (psi)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)			
T351LL/LG075	3/4	19	1.22	31	150	50	0.44
T351LL/LG100	1	25	1.46	37	150	50	0.54
T351LL/LG125	1 1/4	32	1.81	46	150	50	0.78
T351LL/LG150	1 1/2	38	2.05	52	150	50	0.91

*T351 fully complies with the requirements listed in FDA CFR21.

COUPLING SUGGESTIONS: Short shank, long shank couplings (NPT, GHT), barbed inserts attached with bands.

i Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.