



T340AH
Red Cover
T340AA
Black Cover

T340AH / T340AA Series

270 PSI EPDM Braided Steam Hose

GENERAL APPLICATIONS

- High pressure industrial equipment cleaning at refineries, processing plants and shipyards
- Thawing and de-icing of outdoor pipes and other equipment during cold temperatures
- Saturated steam applications up to 270 PSI and 410°F (+210°C)

i Proper draining of steam hose after each use will increase service life.

▲ Use with super heated steam will shorten hose life. Not recommended for washdown applications where detergent or oils are present.

CONSTRUCTION

Tube: Black extruded EPDM – heat-resistant. **Not for steam cleaner use.**

Reinforcement – Single high tensile steel wire braid (1/2" Size), Two high tensile steel wire braids for 3/4" and above.

Cover – Heat-resistant red or black EPDM featuring pin-pricking for venting and wrapped cover fabric impression

SERVICE TEMPERATURE RANGE

Saturated Steam. Constant Operation: -40°F (-40°C) to +410°F (+210°C)
Intermittent to +450°F (+232°C)

BRANDING

ALFAGOMMA – ITALY 340 18 BAR (270 PSI) STEAM – DRAIN AFTER USE – QTR/YEAR (mylar)

View Up To Date Info



◀ SCAN OR VISIT
**KOA.link/
T340AH-AA**

WARNING

Handling steam is very hazardous. If it is not properly controlled it can cause property damage, injury or even death. Selection for the proper application, usage, and maintenance will not only increase hose life but will insure safe operation for the user.

FEATURES AND ADVANTAGES

- **Highest Pressure Capabilities** – Handles pressures up to 270 PSI, higher than other steam hoses which range up to 250.
- **Conductive Tube** – Helps dissipate potential charge to ground, reducing the risk of shocks.
- **Highly Durable Cover** – Heat, weathering, abrasion and ozone resistant cover designed to perform in highly demanding, steam hose applications.

Series Number	ID (in)	ID (mm)	OD (in)	OD (mm)	Max. Working Pressure (psi)	Min. Bending Radius (in) at 68°F	Standard Lengths (ft)	Weight (lbs/each)
T340AA/AH050	1/2	13	0.91	23	270	5	50/100	0.28
T340AA/AH075	3/4	19	1.22	31	270	7 1/2	50/100/200	0.52
T340AA/AH100	1	25	1.50	38	270	10	50/100	0.60
T340AA200	2	51	2.64	67	270	20	50/100	1.38
T340AA250	2 1/2	63	3.19	81	270	25	50	1.99
T340AA300	3	76	3.70	94	270	30	50	2.50

* 10:1 Safety Factor

REFER TO STEAM HOSE TESTING AND INSPECTION ON PAGES 82-84.

PLEASE NOTE: Drain hose after each use to avoid tube damage before hose is put back in operation, to avoid "popcorn" of tube.

i

- Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog
- Universal quick-acting couplings should not be used with steam hose

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.