



T410LL Series

240 PSI Food & Beverage S & D Hose – Crush Resistant

GENERAL APPLICATIONS

- Food and alcoholic beverage suction and discharge
- Hose may be sterilized with +266°F (+130°C) steam for 30 minutes or with 5% soda solution
- Specially designed for wine, beer and spirits, up to 95% alcohol content (190 proof)

▲ Not recommended for dry abrasive materials

CONSTRUCTION

Tube – White nontoxic CIIR – Meets FDA and 3A (18-03) requirements
 Reinforcement – High tensile textile cords with embedded PET helix
 Cover – White EPDM – abrasion and ozone resistant

WORKING PRESSURE

Constant Pressure – 16 Bar (240 PSI)

SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +226°F (+108°C)

BRANDING

ALFAGOMMA – ITALY 410 16 BAR (240 PSI) – FOOD SUCTION & DELIVERY – CRUSH RESISTANT (in black letters)

View Up To Date Info



◀ SCAN OR VISIT
KOA.link/T410LL

3-A
 COMPLIANT
 MATERIAL

Series Number	ID		OD		Max. Working Pressure (psi)	Vacuum Rating Hg (in)	Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)					
T410LL100	1	25	1.46	37	240	30	4	100	0.60
T410LL150	1 1/2	38	2.05	52	240	30	6	100	1.00
T410LL200	2	51	2.56	65	240	30	8	100	1.29
T410LL300	3	76	3.62	92	240	30	12	100	2.23

CONSULT FOOD HOSE GUIDE FOR MATERIAL COMPATIBILITY ON PAGE 37 OF THE ALFAGOMMA INDUSTRIAL RUBBER HOSE CATALOG.

COUPLING SUGGESTIONS: Quick-Acting couplings attached with bands.



Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.