




**THE BREWTT**  
**T422LH Series**  
 Liquid S & D Brewery Hose



**GENERAL APPLICATIONS**

- Brewery suction and discharge
- Liquid food and alcoholic beverage suction and discharge, up to 95% alcohol content (190 proof)
- Versatile hose for applications requiring superb flexibility and light weight, while still maintaining high strength and durability

**CONSTRUCTION**

**Tube** – White Chlorobutyl – meets FDA and 3A (18-03) requirements  
**Reinforcement** – High tensile textile cords with specially designed embedded helix wires  
**Cover** – Red smooth NR/EPDM blend for abrasion and ozone resistance

**SERVICE TEMPERATURE RANGE**

-22°F (-30°C) to +226°F (+108°C)

**BRANDING**

ALFAGOMMA ITALY 422 THE BREWTT 10 bar (150 psi) BREWERY S & D - extra flexible - FDA (white letters)

View Up To Date Info



◀ SCAN OR VISIT  
[KOA.link/T422LH](https://KOA.link/T422LH)



**FEATURES AND ADVANTAGES**

- **Extreme Flexibility** – Uniquely designed for maximum flexibility, bends easily around brewery equipment and works well in tight spaces.
- **Lightweight** – Up to 25% lighter weight than similar rubber hoses, while still maintaining 150 PSI working pressure.
- **High Heat Resistance** - Chlorobutyl tube capable of handling +226°F (+108°C) on a continuous basis. Allows for sterilization with +266°F (+130°C) steam for 30 minutes or with 5% soda solution.
- **High Purity Tube** – Will not impart odor or taste.
- **Smooth Cover** – Designed for easy cleaning, no gaps or crevices for dirt or bacteria to hide. Also provides a smooth surface for clamping.

Series Number	ID		OD		Max. Working Pressure (psi)	Vacuum Rating Hg (in)	Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)					
T422LH075	3/4	19	1.22	31	150	30	1 1/2	100	0.50
T422LH100	1	25	1.54	39	150	30	2	100	0.58
T422LH125	1 1/4	32	1.81	46	150	30	2 1/2	100	0.73
T422LH150	1 1/2	38	2.05	52	150	30	3	100	0.86
T422LH200	2	51	2.56	65	150	30	4	100	1.14
T422LH250	2 1/2	63	3.11	79	150	27	5	100	1.68
T422LH300	3	76	3.62	92	150	27	6	100	2.15

**CONSULT FOOD HOSE GUIDE FOR MATERIAL COMPATIBILITY ON PAGE 37 OF THE ALFAGOMMA INDUSTRIAL RUBBER HOSE CATALOG.**

**COUPLING SUGGESTIONS:** Quick-Acting couplings attached with bands.



Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – [KOA.link/KOA-Couplings-Catalog](https://KOA.link/KOA-Couplings-Catalog)

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.