



T426LB Series **CORRUGATED**

150 PSI Gray Food S & D Hose

GENERAL APPLICATIONS

- Liquid, fatty, oily food and alcoholic beverage, max 75% alcohol content (150 proof), suction and discharge
- Hose may be sterilized with 5% soda solution
- **Not recommended for dry abrasive materials**

CONSTRUCTION

Tube – White NBR – Meets FDA and 3A (18-03) requirements

Reinforcement – High tensile textile cords with flexible steel helix wire

Cover – Corrugated gray NBR/PVC – abrasion, ozone and oil resistant

WORKING PRESSURE

Constant Pressure – 10 Bar (150 PSI)

SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +176°F (+80°C)

BRANDING

ALFAGOMMA – ITALY 426 10 BAR (150 PSI) – GENERAL PURPOSE FOOD QUALITY – S & D (in black letters)

View Up To Date Info



◀ SCAN OR VISIT

KOA.link/T426LB

3-A
COMPLIANT
MATERIAL

Series Number	ID		OD		Max. Working Pressure (psi)	Vacuum Rating Hg (in)	Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)					
T426LB300	3	76	3.62	92	150	30	6	100	1.84
T426LB400	4	102	4.65	118	150	30	8	100	2.69

CONSULT FOOD HOSE GUIDE FOR MATERIAL COMPATIBILITY ON PAGE 37 OF THE ALFAGOMMA INDUSTRIAL RUBBER HOSE CATALOG.

COUPLING SUGGESTIONS: Quick-Acting or combination nipples attached with single bolt, double bolt, wire or band type clamps.

i Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.