



T455LL Series

150 PSI Food Discharge Hose

GENERAL APPLICATIONS

- Discharge of liquid, fatty, oily foods and alcoholic beverages, max 75% alcohol content (150 proof)
- Hose may be sterilized with 5% soda solution
- **Not recommended for dry abrasive materials**

CONSTRUCTION

Tube – White NBR – Meets FDA and 3A (18-03) requirements

Reinforcement – High tensile textile cords

Cover – White NBR/PVC blend – abrasion, ozone and oil resistant

WORKING PRESSURE

Constant Pressure – 10 Bar (150 PSI)

SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +176°F (+80°C)

BRANDING

ALFAGOMMA – ITALY 455 10 BAR (150 PSI) – GENERAL PURPOSE FOOD TRANSFER (in black letters)

View Up To Date Info



◀ SCAN OR VISIT
**KOA.link/
T455LL**

3-A
COMPLIANT
MATERIAL

| Series Number | ID | | OD | | Max. Working Pressure (psi) | Standard Length (ft) | Weight (lbs/ft) |
|---------------|-------|------|------|------|-----------------------------|----------------------|-----------------|
| | (in) | (mm) | (in) | (mm) | | | |
| T455LL150 | 1 1/2 | 38 | 1.89 | 48 | 150 | 100 | 0.60 |
| T455LL200 | 2 | 51 | 2.48 | 63 | 150 | 100 | 0.95 |
| T455LL300 | 3 | 76 | 3.46 | 88 | 150 | 100 | 1.38 |

CONSULT FOOD HOSE GUIDE FOR MATERIAL COMPATIBILITY ON PAGE 37 OF THE ALFAGOMMA INDUSTRIAL RUBBER HOSE CATALOG.

COUPLING SUGGESTIONS: Quick-Acting couplings attached with bands.



Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.