



T452LE Series

150 PSI Potable Water Hose*

**HOSE IS NOT NSF APPROVED*

GENERAL APPLICATIONS

- Discharge of water used for drinking
- Most often used for temporary water lines in construction and industrial applications

CONSTRUCTION

Tube – White NR – Meets FDA and 3A (18-03) requirements
 Reinforcement – High tensile textile cords – 2 ply
 Cover – Blue SBR/EPDM blend – abrasion and ozone resistant

WORKING PRESSURE

Constant Pressure – 10 Bar (150 PSI)

SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +176°F (+80°C)

BRANDING

ALFAGOMMA – ITALY 452 10 BAR POTABLE WATER HOSE (150 PSI) WP (in white letters)

View Up To Date Info



← SCAN OR VISIT
**KOA.link/
 T452LE**

3-A
 COMPLIANT
 MATERIAL

Series Number	ID		OD		Max. Working Pressure (psi)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)			
T452LE150	1 1/2	38	1.97	50	150	100	0.73
T452LE200	2	51	2.56	65	150	100	1.13
T452LE300	3	76	3.62	92	150	100	1.88
T452LE400	4	102	4.65	118	150	100	2.51

CONSULT FOOD HOSE GUIDE FOR MATERIAL COMPATIBILITY ON PAGE 37 OF THE ALFAGOMMA INDUSTRIAL RUBBER HOSE CATALOG.

COUPLING SUGGESTIONS: Quick-Acting couplings attached with bands.

i Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.