



T720LG Series

Bulk Food S & D Hose

GENERAL APPLICATIONS

- Designed for grains, flour and pellet transfer
- Suction and discharge of wet or dry abrasive materials

CONSTRUCTION

Tube – Abrasion resistant, natural white gum rubber 3/16" thick – Meets FDA requirements

Reinforcement – Spiraled high tensile textile cords with flexible steel helix wire and static wire

Cover – Green SBR/EPDM blend – abrasion and ozone resistant

WORKING PRESSURE

Constant Pressure –

- 10 Bar (150 PSI) for 2", 3", 4"
- 5 Bar (75 PSI) for 5", 6", 8"

SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +176°F (+80°C)

BRANDING

ALFAGOMMA – ITALY 720 – BULK FOOD & MATERIAL – S & D (in white letters)

View Up To Date Info



← SCAN OR VISIT
KOA.link/T720LG

3-A
COMPLIANT
MATERIAL

Series Number	ID		OD		Max. Working Pressure (psi)	Vacuum Rating Hg (in)	Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)					
T720LG200	2	51	2.64	67	150	30	6	100	1.23
T720LG300	3	76	3.62	92	150	27	9	100	1.91
T720LG400	4	102	4.65	118	150	27	12	50/100	2.63
T720LG500	5	127	5.71	145	75	24	20	20/50	3.81
T720LG600	6	152	6.69	170	75	24	24	20/50	4.72
T720LG800	8	203	8.78	223	75	21	32	20	7.01

CONSULT FOOD HOSE GUIDE FOR MATERIAL COMPATIBILITY ON PAGE 37 OF THE ALFAGOMMA INDUSTRIAL RUBBER HOSE CATALOG.

Please note: Proper grounding of static wire will prolong tube life.

COUPLING SUGGESTIONS: Quick-Acting or combination nipples attached with single bolt, double bolt, wire or band type clamps



Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.