



## T714LG Series **CORRUGATED** Material Handling Hose FDA Grade

### GENERAL APPLICATIONS

- For suction or discharge of wet or dry abrasive materials
- Suitable for handling materials for human consumption

### CONSTRUCTION

**Tube** – Abrasion resistant, natural white gum rubber 3/16" thick. Meets FDA requirements

**Reinforcement** – Spiraled high tensile textile cords with flexible steel helix wire and static wire

**Cover** – Green corrugated SBR/EPDM blend rubber

### WORKING PRESSURE

Constant Pressure – 5 Bar (75 PSI)

### SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +176°F (+80°C)

### BRANDING

ALFAGOMMA – ITALY 714 – 5 Bar (75 PSI) – BULK FOOD & MATERIAL – S & D (in white letters)

View Up To Date Info



◀ SCAN OR VISIT  
[KOA.link/T714LG](http://KOA.link/T714LG)

**3-A**  
COMPLIANT  
MATERIAL

Series Number	ID		OD		Max. Working Pressure (psi)	Vacuum Rating Hg (in)	Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)					
T714LG500	5	127	5.63	143	75	24	12 1/2	20/50	3.8
T714LG600	6	152	6.85	174	75	24	24	20/50	4.75
T714LG800	8	203	8.94	227	75	21	32	20	7.01

**CONSULT FOOD HOSE GUIDE FOR MATERIAL COMPATIBILITY ON PAGE 37 OF THE ALFAGOMMA INDUSTRIAL RUBBER HOSE CATALOG.**

*Please note: Proper grounding of static wire will prolong tube life.*

**COUPLING SUGGESTIONS:** Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.



Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – [KOA.link/KOA-Couplings-Catalog](http://KOA.link/KOA-Couplings-Catalog)

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.