



T760LE Series

75 PSI Dry Bulk Food Discharge Hose

GENERAL APPLICATIONS

- Discharge or delivery of dry bulk food products

CONSTRUCTION

Tube – 3/16" white NR – abrasion resistant – Meets FDA requirements

Reinforcement – Spiraled high tensile textile cords with static wire

Cover – Blue SBR/EPDM – abrasion and ozone resistant

WORKING PRESSURE

Constant Pressure – 5 Bar (75 PSI)

SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +176°F (+80°C)

BRANDING

ALFAGOMMA – ITALY 760 5 BAR (75 PSI) – BULK FOOD & MATERIAL DELIVERY (in white letters)

View Up To Date Info



◀ SCAN OR VISIT
KOA.link/T760LE

3-A
COMPLIANT
MATERIAL

Series Number	ID		OD		Max. Working Pressure (psi)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)			
T760LE400	4	102	4.65	118	75	100	2.12

CONSULT FOOD HOSE GUIDE FOR MATERIAL COMPATIBILITY ON PAGE 37 OF THE ALFAGOMMA INDUSTRIAL RUBBER HOSE CATALOG.

Please note: Proper grounding of static wire will prolong tube life.

COUPLING SUGGESTIONS: Quick-Acting coupling attached with bands

i Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.