



T6D1AA Series

400 PSI Oil Rigger / Frac Discharge Hose

GENERAL APPLICATIONS

- Crude oil delivery in oil field and gas exploration
- Fracking fluids
- Liquid mud

CONSTRUCTION

Tube – Black synthetic elastomer

Reinforcement – High tensile textile cords

Cover – Black synthetic elastomer – abrasion, oil and ozone resistant

WORKING PRESSURE

Constant Pressure – 27 Bar (400 PSI)

SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +176°F (+80°C)

BRANDING

ALFAGOMMA – ITALY OIL RIGGER – FRAC 27 BAR (400 PSI)
(in blue letters)

View Up To Date Info



← SCAN OR VISIT
**KOA.link/
T6D1AA**

Series Number	ID		OD		Max. Working Pressure (psi)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)			
T6D1AA400	4	102	4.72	120	400	100	2.89



Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.