



## CT601AA Series **CORRUGATED**

150 PSI Corrugated Oil Rigger/Oil Field-Frac Tank Hose

### GENERAL APPLICATIONS

- Frac solutions and slurries
- Handling crude oil
- Oil field vacuum tank service

*Note: For applications up to 35% aromatics. Not for use with refined petroleum products*

### CONSTRUCTION

**Tube** – Black Nitrile – PVC blend, limited oil resistance, for oil field use

**Reinforcement** – High tensile textile cords with flexible steel helix wire

**Cover** – Black corrugated SBR – abrasion, ozone, limited oil resistance

### WORKING PRESSURE

Constant Pressure – 10 Bar (150 PSI)

### SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +176°F (+80°C)

### BRANDING

ALFAGOMMA – ITALY 6C1 10 BAR (150 PSI) OIL FIELD-FRAC TANK S & D (in blue letters)

View Up To Date Info



← SCAN OR VISIT  
**KOA.link/  
CT601AA**

Series Number	ID		OD		Max. Working Pressure (psi)	Vacuum Rating Hg (in)	Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)					
CT601AA200	2	51	2.40	61	150	30	6	100	0.86
CT601AA300	3	76	3.46	88	150	27	9	100	1.61
CT601AA400	4	102	4.49	114	150	27	12	100	2.39

**COUPLING SUGGESTIONS:** Quick-Acting couplings or combination nipples attached with bands.

**i** Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.