



## T601AA Series

### 150 PSI Oil Rigger/Oil Field-Frac Tank Hose

#### GENERAL APPLICATIONS

- Frac solutions and slurries
- Handling crude oil
- Oil field vacuum tank service

*Note: For applications up to 35% aromatics. Not for use with refined petroleum products*

#### CONSTRUCTION

**Tube** – Black Nitrile – PVC blend, limited oil resistance, for oil field use

**Reinforcement** – High tensile textile cords with flexible steel helix wire

**Cover** – Black SBR – abrasion, ozone, limited oil resistance

#### WORKING PRESSURE

Constant Pressure – 10 Bar (150 PSI)

#### SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +176°F (+80°C)

#### BRANDING

ALFAGOMMA – ITALY 601 10 BAR (150 PSI) OIL FIELD-FRAC TANK HOSE (in blue letters)

View Up To Date Info



← SCAN OR VISIT  
[KOA.link/  
T601AA](https://KOA.link/T601AA)

Series Number	ID		OD		Max. Working Pressure (psi)	Vacuum Rating Hg (in)	Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)					
T601AA200	2	51	2.40	61	150	30	10	100	0.93
T601AA300	3	76	3.46	88	150	27	15	100	1.73
T601AA400	4	102	4.57	116	150	27	20	100	2.40
T601AA600	6	152	6.61	168	150	24	30	20/100	4.59

**COUPLING SUGGESTIONS:** Quick-Acting couplings or combination nipples attached with bands.



Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – [KOA.link/KOA-Couplings-Catalog](https://KOA.link/KOA-Couplings-Catalog)

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.