



## 6C5AA Series **CORRUGATED**

### 150 PSI Corrugated Tank Truck Hose

#### GENERAL APPLICATIONS

- For suction and discharge applications in truck and tank car transfer of gasoline, oil and other petroleum-based products with up to 50% aromatic content
- Not SAE100R4 rated

#### CONSTRUCTION

Tube – Black Conductive NBR

Reinforcement – High tensile textile cords with flexible steel helix wire

Cover – Black corrugated CR – abrasion, ozone, and hydrocarbon resistant

#### WORKING PRESSURE

Constant Pressure – 10 Bar (150 PSI)

#### SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +176°F (+80°C)

#### BRANDING

ALFAGOMMA – ITALY 6C5 10 BAR (150 PSI) PETROLEUM TANK TRUCK (in red letters)

View Up To Date Info



← SCAN OR VISIT  
**KOA.link/  
6C5AA**

Series Number	ID		OD		Max. Working Pressure (psi)	Vacuum Rating Hg (in)	Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)					
6C5AA200	2	51	2.48	63	150	30	4	100	0.85
6C5AA300	3	76	3.44	90	150	27	6	100	1.57
6C5AA400	4	102	4.57	116	150	27	8	100	2.21
6C5AA600	6	152	6.54	166	150	27	12	20	3.59

**COUPLING SUGGESTIONS:** Quick-Acting couplings or combination nipples attached with bands.



Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.