



## T605AH Series

### 150 PSI Red Petroleum S & D Hose

#### GENERAL APPLICATIONS

- For suction and discharge applications in truck and tank car transfer of gasoline, oil and other petroleum-based products with up to 50% aromatic content

#### CONSTRUCTION

Tube – Black conductive NBR

Reinforcement – High tensile textile cords with flexible steel helix wire

Cover – Red CR – abrasion, ozone and hydrocarbon resistant

#### WORKING PRESSURE

Constant Pressure – 10 Bar (150 PSI)

#### SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +176°F (+80°C)

#### BRANDING

ALFAGOMMA – ITALY 605 – 10 BAR (150 PSI) PETROLEUM – S & D (in yellow letters)

**⚠ Not recommended for use on a reel**

**⚠ Not recommended for gasoline/high additives**

**ℹ Diesel #1 or #2 are approved for use**

View Up To Date Info



← SCAN OR VISIT  
**KOA.link/  
T605AH**

Series Number	ID		OD		Max. Working Pressure (psi)	Vacuum Rating Hg (in)	Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)					
T605AH150	1 1/2	38	1.89	48	150	30	6	100	0.73
T605AH200	2	51	2.40	61	150	30	8	100	0.94
T605AH300	3	76	3.46	88	150	27	12	100	1.74
T605AH400	4	102	4.57	116	150	27	16	100	2.41

**COUPLING SUGGESTIONS:** Quick-Acting, combination nipples attached with bands or internally expanded brass couplings with gasket seal attached with ferrules.

**i** Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.