



## T606AE Series **CORRUGATED** 150 PSI Corrugated Petroleum S & D – Arctic Hose

### GENERAL APPLICATIONS

- For suction and discharge applications in truck and tank car transfer of gasoline, oil and other petroleum-based products with up to 50% aromatic content
- Can handle glycols
- Where extreme flexibility is needed in low temperature

### CONSTRUCTION

Tube – Black conductive NBR

Reinforcement – High tensile textile cords with flexible steel helix wire

Cover – Blue CR corrugated – abrasion, ozone and hydrocarbon resistant

### WORKING PRESSURE

Constant Pressure – 150 PSI

### SERVICE TEMPERATURE RANGE

-65°F (-54°C) to +180°F (+82°C)

### BRANDING

ALFAGOMMA – ITALY 606 – 10 BAR (150 PSI) PETROLEUM – S & D Arctic (in yellow letters on blue layline)

View Up To Date Info



← SCAN OR VISIT  
**KOA.link/  
T606AE**

Series Number	ID		OD		Max. Working Pressure (psi)	Vacuum Rating Hg (in)	Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)					
T606AE200	2	51	2.48	63	150	30	3	100	1.06
T606AE300	3	76	3.54	90	150	30	4 1/2	100	1.84
T606AE400	4	102	4.57	116	150	30	6	100	2.67

**COUPLING SUGGESTIONS:** Quick-Acting, combination nipples attached with bands or internally expanded brass couplings with gasket seal attached with ferrules.



Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.