



T620AA Series

300 PSI Black Fuel & Oil S & D Hose

GENERAL APPLICATIONS

- Designed for heavy duty applications
- Fuel and oil suction and discharge for up to 50% aromatic content
- Suitable for diesel fuels and oils

CONSTRUCTION

Tube – Black conductive NBR

Reinforcement – High tensile textile cords with steel helix wire and static wire

Cover – Black conductive CR – abrasion, ozone, hydrocarbon, and UV resistant

WORKING PRESSURE

Constant Pressure – 20 Bar (300 PSI)

SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +176°F (+80°C)

BRANDING

ALFAGOMMA – ITALY 620 – 20 BAR (300 PSI) PETROLEUM – S & D Ω (in red letters)

View Up To Date Info



← SCAN OR VISIT
**KOA.link/
T620AA**

Series Number	ID		OD		Max. Working Pressure (psi)	Vacuum Rating Hg (in)	Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)					
T620AA200	2	51	2.48	63	300	30	8	100	1.10
T620AA300	3	76	3.54	90	300	27	12	100	1.77
T620AA400	4	102	4.57	116	300	27	16	100	2.43
T620AA600	6	152	6.69	170	300	24	24	20/100	5.60
T620AA800	8	203	8.86	225	300	21	32	20	9.24

COUPLING SUGGESTIONS: Quick-Acting, combination nipples attached with bands or internally expanded brass couplings with gasket seal attached with ferrules.

i Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.