



T650AH Series

150 PSI Oil Discharge Hose

GENERAL APPLICATIONS

- Oil discharge hose designed for use on trucks, docks or barges where a soft wall hose is required

CONSTRUCTION

Tube – Black conductive NBR

Reinforcement – Spiraled high tensile textile cords with embedded static wire

Cover – Red CR – abrasion, ozone and hydrocarbon resistant

WORKING PRESSURE

Constant Pressure – 10 Bar (150 PSI)

SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +176°F (+80°C)

BRANDING

ALFAGOMMA – ITALY 650 10 BAR (150 PSI) – PETROLEUM DELIVERY (in yellow letters)

i No certification for marine applications

View Up To Date Info



← SCAN OR VISIT
**KOA.link/
T650AH**

Series Number	ID		OD		Max. Working Pressure (psi)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)			
T650AH150	1 1/2	38	1.97	50	150	100	0.77
T650AH200	2	51	2.40	61	150	100	0.82
T650AH300	3	76	3.46	88	150	100	1.42
T650AH400	4	102	4.49	114	150	100	1.92

COUPLING SUGGESTIONS: Quick-Acting or combination nipples attached with bands.

i Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.