



T654AA EVOLUTION Series

Small Engine Fuel Transfer Hose SAE J30R7

GENERAL APPLICATIONS

- Boat engines
- Designed for small engine marine and automotive fuel and oil transfer applications
- Generators
- Lawnmowers
- Pressure washers
- Snowmobiles

CONSTRUCTION

Tube – Conductive Nitrile (NBR)
 Reinforcement – High tensile textile braids
 Cover – Conductive Neoprene (CR) hydrocarbon resistant

WORKING PRESSURE

Constant Pressure – 20 bar (300 PSI)

SERVICE TEMPERATURE RANGE

-40°F (-40°C) to +257°F (+125°C)

BRANDING

ALFAGOMMA-ITALY- 654 EVOLUTION 20 bar (300 psi) MULTI FUEL SAE 30R7 ID mm– QQ/YY (white inkjet lettering)

View Up To Date Info



← SCAN OR VISIT
[KOA.link/
 T654AA](https://KOA.link/T654AA)

FEATURES AND ADVANTAGES

- **Broad Fuel Resistance** – Exhibits resistance to a wide range of fuels. Meets SAE J30R7 compliance, meaning it can be used in a variety of fuel applications including gasoline, oil, diesel fuel and lubrication for internal combustion engines in mobile, stationary and marine applications.
- **Comprehensive Small Size Range** – Wide variety of small sizes available starting at 3/16" all the way up to 1".
- **High Kink Resistance** – Possesses a highly durable construction for a soft wall hose; resists the kinking, ovaling and elongation that can affect similar spaghetti style hoses.
- **Easy Installation** – Flexible and lightweight construction for ease of installation in tight spaces.
- Also for bio-fuels and bio-diesels.

Series Number	ID (in)	ID (mm)	OD (in)	OD (mm)	Max. Working Pressure (psi)	Standard Reel* Length (ft)	Weight (lbs/ft)
T654AA019	3/16	5	0.47	12	300	950	0.07
T654AA025	1/4	6	0.51	13	300	820	0.09
T654AA031	5/16	8	0.59	15	300	720	0.11
T654AA038	3/8	10	0.67	17	300	620	0.12
T654AA050	1/2	13	0.79	20	300	600	0.15
T654AA062	5/8	16	0.94	24	300	450	0.21
T654AA075	3/4	19	1.06	27	300	330	0.23
T654AA100	1	25	1.34	34	300	220	0.34

COUPLING SUGGESTIONS: Tubular steel full flow male permanently swaged or internally expanded with ferrule to provide maximum hose coupling compatibility.

† 3-to-1 safety factor

* Up to three pieces (min. 30' length) per reel

i Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.