



## T631AE Series

### 300 PSI Hydrocarbon Drain Hose

#### GENERAL APPLICATIONS

- Drain hose for residue from cleaning storage tanks and refining hydrocarbons

#### CONSTRUCTION

Tube – Black NBR-hydrocarbon resistant

Reinforcement – High tensile steel wire braids

Cover – Blue CR – abrasion and hydrocarbon resistant

#### WORKING PRESSURE

Constant Pressure – 20 Bar (300 PSI)

#### SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +356°F (+180°C)

#### BRANDING

ALFAGOMMA 631-HYDROCARBON DRAIN HOSE-300PSI (in blue letters on green layline)

View Up To Date Info



← SCAN OR VISIT  
**KOA.link/  
T631AE**

Series Number	ID		OD		Wall Thickness (mm)	Max. Working Pressure (psi)	Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)					
T631AE075	3/4	19	1.26	32	6	300	3	50/100	0.50

**COUPLING SUGGESTIONS:** Permanently attached couplings are suggested for assemblies.



Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.