



T614AA Series

150 PSI Hot Tar & Asphalt S & D Hose

GENERAL APPLICATIONS

- Conveying hot non-FDA oils
- Hot tar and asphalt suction and discharge service

CONSTRUCTION

Tube – Black NBR – hot tar and asphalt resistant

Reinforcement – High tensile textile cords with steel helix wire

Cover – Black CSM – abrasion, ozone and hot tar resistant

WORKING PRESSURE

Constant Pressure – 10 Bar (150 PSI)

SERVICE TEMPERATURE RANGE

-4°F (-20°C) to +356°F (+180°C)

BRANDING

ALFAGOMMA – ITALY 614 10 BAR (150 PSI) HOT TAR AND ASPHALT (in black letters on red layline - mylar)

View Up To Date Info



◀ SCAN OR VISIT

**KOA.link/
T614AA**

Series Number	ID (in)	ID (mm)	OD (in)	OD (mm)	Wall Thickness (mm)	Max. Working Pressure (psi)	Vacuum Rating Hg (in)	Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
T614AA200	2	51	2.72	69	9	150	30	10	100	1.64
T614AA300	3	76	3.78	96	10	150	27	15	100	2.69
T614AA400	4	102	4.80	122	10	150	27	20	100	3.57

COUPLING SUGGESTIONS: Permanently attached couplings are suggested for assemblies.

i Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.