



T631AA Series

300 PSI Hot Tar & Asphalt Applicator Delivery Hose

GENERAL APPLICATIONS

- Hot tar and asphalt delivery service

CONSTRUCTION

Tube – Black NBR – hot tar and asphalt resistant

Reinforcement – High tensile steel wire braids

Cover – Black CR – abrasion, ozone, hydrocarbon and fire resistant

WORKING PRESSURE

Constant Pressure – 20 Bar (300 PSI)

SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +356°F (+180°C)

BRANDING

AALFAGOMMA – ITALY 631 20 BAR (300 PSI) HOT TAR AND ASPHALT (in white letters - mylar)

SAFETY FACTOR

10:1

View Up To Date Info



← SCAN OR VISIT
**KOA.link/
T631AA**

Series Number	ID		OD		Wall Thickness (mm)	Max. Working Pressure (psi)	Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)					
T631AA075	3/4	19	1.26	32	6	300	3	50/100	0.50
T631AA100	1	25	1.50	38	6	300	3	50/100	0.77

COUPLING SUGGESTIONS: Permanently attached couplings are suggested for assemblies.



Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.