



CONQUEROR™

T740AA Series

1500 PSI High Performance Steel Reinforced Concrete Pumping Hose

GENERAL APPLICATIONS

- Heavy-duty, steel-reinforced construction for use on concrete boom pumps and other demanding applications

CONSTRUCTION

Tube – Black conductive NR – abrasion resistant

Reinforcement – High tensile steel cords

Cover – Black conductive SBR/NR blend – abrasion and ozone resistant

WORKING PRESSURE

Constant Pressure – 100 Bar (1500 PSI)

SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +176°F (+80°C)

BRANDING

ALFAGOMMA – ITALY 740 100 BAR (1500 PSI) W. P. HEAVY DUTY CONCRETE PUMPING (in yellow letters)

View Up To Date Info



◀ SCAN OR VISIT

**KOA.link/
T740AA**

Series Number	ID		OD		Wall Thickness (mm)	Max. Working Pressure (psi)	Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)					
T740AA200	2	51	2.72	69	9	1500	10	50/100	1.44
T740AA250	2 1/2	63	3.35	85	11	1500	10 1/2	50/100	2.25
T740AA300	3	76	3.94	100	12	1500	15	50/100	3.06
T740AA400	4	102	5.04	128	13	1500	20	10/50/100	4.72
T740AA500	5	127	6.10	155	14	1500	25	10/50	6.95

COUPLING SUGGESTIONS: CHC-CA Series "California Style" or CHC-US Series "Victaulic Style" couplings (see page 247 in the KOA Couplings and Accessories catalog)



Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.