



## T720AA Series

### Bulk Material S & D Hose

#### GENERAL APPLICATIONS

- Designed for grains and dry cement
- Suction and discharge of wet or dry abrasive materials

#### CONSTRUCTION

**Tube** – 3/16" black conductive NR – abrasion resistant

**Reinforcement** – Spiraled high tensile textile cords with flexible steel helix wire

**Cover** – Black conductive SBR/NR blend – abrasion and ozone resistant

#### WORKING PRESSURE

Constant Pressure –

10 Bar (150 PSI) for 2", 3", 4"

5 Bar (75 PSI) for 5", 6", 8"

#### SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +176°F (+80°C)

#### BRANDING

ALFAGOMMA – ITALY 720 – BULK MATERIAL – S & D (in white letters)

View Up To Date Info



← SCAN OR VISIT

**KOA.link/  
T720AA**

| Series Number | ID (in) | ID (mm) | OD (in) | OD (mm) | Max. Working Pressure (psi) | Vacuum Rating Hg (in) | Min. Bending Radius (in) at 68°F | Standard Length (ft) | Weight (lbs/ft) |
|---------------|---------|---------|---------|---------|-----------------------------|-----------------------|----------------------------------|----------------------|-----------------|
| T720AA200     | 2       | 51      | 2.56    | 65      | 150                         | 30                    | 6                                | 100                  | 0.97            |
| T720AA300     | 3       | 76      | 3.54    | 90      | 150                         | 27                    | 9                                | 100                  | 1.54            |
| T720AA400     | 4       | 102     | 4.57    | 116     | 150                         | 27                    | 12                               | 50/100               | 2.15            |
| T720AA500     | 5       | 127     | 5.63    | 143     | 75                          | 24                    | 20                               | 20/50                | 3.20            |
| T720AA600     | 6       | 152     | 6.61    | 168     | 75                          | 24                    | 24                               | 20/50                | 4.01            |
| T720AA800     | 8       | 203     | 8.70    | 221     | 75                          | 21                    | 32                               | 20                   | 6.05            |

**COUPLING SUGGESTIONS:** Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.



Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.