



T755AA Series*

* Formerly LT753AA

180 PSI 2-Ply Abrasive Material Blast Hose

GENERAL APPLICATIONS

- Designed to convey abrasives, sand and shot blast material

CONSTRUCTION

Tube – Black static conducting NR – offering excellent abrasion resistance, upgraded to 36mm³ (cubed) rating

Reinforcement – High tensile textile cords – 2-ply construction

Cover – Black conductive SBR/NR blend – abrasion and ozone resistant – pin pricked

WORKING PRESSURE

Constant Pressure – 12 Bar (180 PSI)

SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +176°F (+80°C)

BRANDING

ALFAGOMMA – ITALY - 755 12 BAR (180 PSI) TOP ABRASIVE MATERIAL BLAST Ω (in white letters)

View Up To Date Info



← SCAN OR VISIT
[KOA.link/
T755AA](https://KOA.link/T755AA)

Series Number	ID		OD		Tube Thickness (mm)	Max. Working Pressure (psi)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)				
T755AA050	1/2	13	1.06	27	0.212	180	50/100	0.34
T755AA125	1 1/4	32	1.89	48	0.240	180	50/100	0.77

NOTES:

- Tolerances according to RMA Class 311-A

BLASTING DATA GUIDE

Premature hose wear can be prevented if the proper nozzle size is used for the corresponding hose ID size. (See chart below)

Series	UB8	UB7	UB6	UB5	UB4
CFM @ 100 PSI	350	260	200	150	90
AIR HOSE	2	1 1/2	1 1/2	1 1/4	1 1/4
S.B. HOSE SIZE	1 1/2	1 1/2	1 1/4	1 1/4	1
MAT. LB/HR	2250	1750	1260	900	540

i Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – KOA.link/KOA-Couplings-Catalog

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.