



## T757AA / T737AA Series\*

\* T737AA for 3" ID

### 600 PSI Plaster & Concrete Hose

#### GENERAL APPLICATIONS

- Designed for pumping plaster, grout, and wet cement to placement sites

#### CONSTRUCTION

Tube – Black conductive NR – abrasion resistant

Reinforcement – High tensile textile cords

Cover – Black conductive SBR/NR – abrasion and ozone resistant

#### WORKING PRESSURE

Constant Pressure – 40 Bar (600 PSI)

#### SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +176°F (+80°C)

#### BRANDING

ALFAGOMMA – ITALY 757 – 40 BAR (600 PSI) PLASTER & CONCRETE (in white letters) and ALFAGOMMA – ITALY 737 – 40 BAR (600 PSI) PLASTER & CONCRETE (in white letters)

View Up To Date Info



← SCAN OR VISIT  
[KOA.link/  
T757-37AA](https://KOA.link/T757-37AA)

Series Number	ID		OD		Max. Working Pressure (psi)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)			
T757AA150	1 1/2	38	2.13	54	600	100	0.82
T757AA200	2	51	2.64	67	600	100	1.09
T737AA300	3	76	4.09	104	600	100	2.96

**COUPLING SUGGESTIONS:** Tubular steel full flow male permanently swaged or internally expanded with ferrule to provide maximum hose coupling compatibility.



Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – [KOA.link/KOA-Couplings-Catalog](https://KOA.link/KOA-Couplings-Catalog)

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.