



T758AA  
Black Cover



T758AE  
Blue Cover

## T758AA / T758AE Series

### 800 PSI Plaster, Grout & Concrete Hose

#### GENERAL APPLICATIONS

- Designed for pumping plaster, grout, wet cement to construction placement sites at rated pressures

#### CONSTRUCTION

Tube – Black conductive NR – abrasion-resistant

Reinforcement – Spiraled high tensile textile cords

Cover – Black SBR/NR. Blue SBR/EPDM

#### WORKING PRESSURE

Constant Pressure – 55 Bar (800 PSI)

#### SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +176°F (+80°C)

#### BRANDING

ALFAGOMMA – ITALY 758 – 55 BAR (800 PSI) PLASTER & CONCRETE (in white letters)

View Up To Date Info



← SCAN OR VISIT  
[KOA.link/  
T758AA-AE](https://KOA.link/T758AA-AE)

Series Number	ID		OD		Max. Working Pressure (psi)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)			
T758AA/AE100	1	25	1.57	40	800	100	0.60
T758AA/AE125	1 1/4	32	1.93	49	800	100	0.85
T758AA/AE150	1 1/2	38	2.28	58	800	100	1.15
T758AA/AE200	2	51	2.80	71	800	100	1.49

**COUPLING SUGGESTIONS:** Tubular steel full flow male permanently swaged or internally expanded with ferrule to provide maximum hose coupling compatibility.

**i** Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type – [KOA.link/KOA-Couplings-Catalog](https://KOA.link/KOA-Couplings-Catalog)

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.